

MTG-100 Sett

Komplett system 12 enheter Lader ISM

Model MTG-100T

Name	UHF Rechargeable Battery Digital Transmitter
Power Supply	Built-in lithium-ion battery
Housing	Ultra-compact, pocket-sized
Display	LCD with advanced function settings and battery status.
Frequency Range	863 ~ 865 MHz ISM band.
Modulation Type	Digital modulation
Preset Channels	16 preset channels. At least 3 or 4 compatible channels for different tour groups can be used simultaneously at the same place.
Channel Setup	Manual ACT sync or via MTG-100C-12 or MTG-100C-12- charger carry case.
Optional	Microphones MM-10, MM-202P, MU-101P, MU-53HNP, MU-23P
Dimensions	45 × 84 × 21 mm (W×H×D)
WeightApprox.	51 g
Note	Refer to the actual product in the event of product description discrepancy.

Model MTG-100R

Name	UHF Rechargeable Battery Digital
Power Supply	Built-in lithium-ion battery
Housing	Ultra-compact, pocket-sized.
Display	LCD with advanced function settings and battery status.
Frequency Range	863 ~ 865 MHz ISM bands.
Modulation Type	Digital modulation
Name	UHF Rechargeable Battery Digital Receiver
Power Supply	Built-in lithium-ion battery
Housing	Ultra-compact, pocket-sized.

Display	LCD with advanced function settings and battery status.
Frequency Range	863 ~ 865 MHz ISM bands.
Modulation Type	Digital modulation
Preset Channels	16 preset channels. At least 3 compatible channels for different tour groups can be used simultaneously at the same place.
Channel Setup	Manual ACT sync or via MTG-100C-12 or MTG-100C-12
Receiving Mode	True diversity receiving with proprietary built-in dual antennas.
Earphones	E-5S, E-10S, E-20S (optional)
Dimensions	45 × 84 × 21 mm (W×H×D)
Weight	Approx. 67 g
Note	Refer to the actual product in the event of product description discrepancy.

Model MTG-100C-12

Name	12-slot Charger and Storage Case
Charging Slot	10 receivers & 2 transmitters
Charge Time	< 4 hours
Max. Power	
Consumption	26 W
Dimensions	403 × 133 × 306 mm (W×H×D)
Weight	Approx. 4.9 kg
Note	Refer to the actual product in the event of product description discrepancy.

Model E-20S

Name	Stereo Headphones
Driver Unit	∅ 30 mm
Frequency Response	20 Hz ~ 20 kHz
Sensitivity	105 dB ± 3 dB at 1 mW
Max. Input Power	100 mW

Impedance	24 Ω at 1 kHz 1 mW
Connector	\varnothing 3.5 mm phone jack
Cable Length	120 cm
Weight	Approx. 64 g
Note	Refer to the actual product in the event of product description discrepancy.

Model MU-53HNP

Name	Headworn Microphone
Capsule	\varnothing 10 mm Uni-directional ECM
Frequency Response	50 Hz ~ 18 kHz
Max. SPL	136 dB
Sensitivity	-46 dBV \pm 3 dB
Connector	\varnothing 3.5 mm phone jack
Length	150 cm
Weight	Approx. 24 g
Note	Refer to the actual product in the event of product description discrepancy.