



MTP/MPO

LinkIT MTP/MPO-A OS2 24c 5m
USConec MTP Female-Female | LSZH

Product number: MTP24OS2-050-A

Product Description

This MPO / MTP fiber optic trunk cable houses 24 fibers. The OS2 multi cable is 3mm in diameter, comes in Yellow color and is halogen free (LSZH). The cable consists of MTP connectors from USConec. Typical Insertion Loss 0.25dB, Optical Return Loss > 60dB and Maximum tensile, long-term: 80 N. Maximum length with OS2 cable is limited by which transceivers are used. MPO cable is delivered in the length you want, to order. For less expensive solution, cable with MPO connectors can be supplied on request. MPO and MTP are 100% compatible. If the best flame retardant cable is desired, we can supply the OFNP version, which has the best rating.

Main Specifications

| | |
|---------------------------|--------------------|
| Brand | LinkIT |
| Color | Yellow |
| Length (m) | 5 |
| Category | OS2 24 fiber |
| Connector type 1 | MTP/MPO F |
| Connector type 2 | MTP/MPO F |
| Number of fibers | 24 |
| Wave length (nm) | 1310/1550nm |
| Core Diameter (um) | 9/125 - Singlemode |



Extended Specifications

| | |
|---------------------------------|----------|
| Jacket material | LSZH |
| Optical Return Loss (dB) | >= 50 dB |
| Insertion Loss (dB) | <= 70 dB |
| Operating Temperature | -20-+70 |
| Storage Temperature | -20-+70 |
| Cable Diameter (mm) | 2 |
| Halogenfree | ✓ |
| Bending radius (mm) | 20 |
| Tensile loads (N) | 80N |
| Certifications | CE, RoHS |

Single packaging

| | |
|--------------------------|-------|
| Unit | PCE |
| Quantity | 1 |
| Height (cm) | 20,32 |
| Width (cm) | 20,32 |
| Length(cm) | 20,32 |
| Weight (kg) | 0,147 |
| Gross Weight (kg) | 0,15 |



Dimensional Sketches

● Type A-24 Fibers

