

HDMI 2.0



Elivi HDMI 2.0 4K@60 1,5 m

High Speed, Ethernet, 4Kx2@60Hz, AWG 30

Product number: ELV-HDMI20-MM-015

Product Description

The Elivi HDMI 2.0 4K@60 High Speed cable supports up to 4K resolution at 60Hz, providing exceptional video quality for demanding applications like home entertainment and professional presentations. The cable features Ethernet support, allowing you to connect networked devices without using extra cables, offering a more convenient and streamlined setup. With high-speed data transfer, it is perfect for audio and video applications that require reliable and fast performance. This cable is an ideal choice for both personal and professional users seeking a reliable, high-performance HDMI solution.

Main Specifications

Brand	Elivi
Color	Black
Length (m)	1,5
Connector type 1	HDMI AM
Connector type 2	HDMI AM
HDMI version	HDMI 2.0
Max Resolution	4Kx2K@60Hz



Extended Specifications

AWG wire size	30
Jacket material	Black PVC
Anti-kink sleeve	Moulded PVC
Outer Cape diameter	6
Connector contact plating	Gold plated
Certifications	CE, REACH, RoHS

Single packaging

Unit	PCE
Quantity	1



Dimensional Sketches

Rev.No	Revision note	Date	Signature	Checked																																																																										
<table border="1" style="margin: auto;"> <thead> <tr> <th>P/N</th> <th>L/mm</th> <th>T/mm</th> </tr> </thead> <tbody> <tr> <td>134084 ELY-HDMI20-MM-005</td> <td>500</td> <td>10</td> </tr> <tr> <td>134085 ELY-HDMI20-MM-010</td> <td>1000</td> <td>20</td> </tr> <tr> <td>134086 ELY-HDMI20-MM-015</td> <td>1500</td> <td>20</td> </tr> <tr> <td>134087 ELY-HDMI20-MM-020</td> <td>2000</td> <td>30</td> </tr> </tbody> </table>					P/N	L/mm	T/mm	134084 ELY-HDMI20-MM-005	500	10	134085 ELY-HDMI20-MM-010	1000	20	134086 ELY-HDMI20-MM-015	1500	20	134087 ELY-HDMI20-MM-020	2000	30																																																											
P/N	L/mm	T/mm																																																																												
134084 ELY-HDMI20-MM-005	500	10																																																																												
134085 ELY-HDMI20-MM-010	1000	20																																																																												
134086 ELY-HDMI20-MM-015	1500	20																																																																												
134087 ELY-HDMI20-MM-020	2000	30																																																																												
<p>Electronic Tests:</p> <ol style="list-style-type: none"> 1. Open/Short/Intermittence: 100% 2. Insulation Resistance: DC300V 0.01S 10MΩ (Min) 3. Conductive Resistance: 5Ω (Max) 4. Resolution: 4K*2K@60Hz 5. RoHS & REACH COMPLIANT 																																																																														
<p>PIN OUT</p>																																																																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td>① LABEL</td> <td>LABEL L*W=80*15 WHIT ELIVI LOGO</td> <td>1</td> <td>PCS</td> <td>①</td> <td>Quantity</td> <td colspan="3">Title/Name, designation, material, dimension etc</td> <td colspan="2">Article NO./Reference</td> </tr> <tr> <td>② DUST CAP</td> <td>HDMI A MALE DUST CAP</td> <td>2</td> <td>PCS</td> <td>②</td> <td>Designed by</td> <td>Checkde by</td> <td>Approved by - date</td> <td>File name</td> <td>Date</td> <td>Scale</td> </tr> <tr> <td>③ MOLDED</td> <td>45P BLACK PVC</td> <td></td> <td>G</td> <td>③</td> <td>FLY</td> <td>HELEN</td> <td>2025, 01. 21</td> <td></td> <td>2025, 01. 21</td> <td>FREE</td> </tr> <tr> <td>④ MOLDED</td> <td>LDPE</td> <td></td> <td>G</td> <td>④</td> <td colspan="5" rowspan="2" style="text-align: center;"> </td> <td colspan="2" rowspan="2" style="text-align: center;">HDMI2.0 AM-AM</td> </tr> <tr> <td>⑤ CONNECTOR</td> <td>HDMI A MALE, GOLD PLATED PIN, BLACK INSULATION, GOLD PLATED SHELL</td> <td>2</td> <td>PCS</td> <td>⑤</td> </tr> <tr> <td>⑥ CABLE</td> <td>[1/0.254BC*1P-D(1/0.254BC)*FAM]45C*1/0.254BC*4C*AL-D(1/0.254BC)*B(1/6*5/0.12AL-MG) BLACK PVC JACKET, OD: 6.0±0.2mm MARKING: High Speed HDMI Cable with Ethernet</td> <td>L</td> <td>MM</td> <td>⑥</td> <td>ANGLE: </td> <td colspan="4"></td> <td>Edition</td> <td>Sheet</td> </tr> <tr> <td>NO.</td> <td>MATERIAL</td> <td colspan="2">DESCRIPTION</td> <td>QTY.</td> <td>UNIT</td> <td colspan="4"></td> <td>1</td> <td>1/1</td> </tr> </tbody> </table>					① LABEL	LABEL L*W=80*15 WHIT ELIVI LOGO	1	PCS	①	Quantity	Title/Name, designation, material, dimension etc			Article NO./Reference		② DUST CAP	HDMI A MALE DUST CAP	2	PCS	②	Designed by	Checkde by	Approved by - date	File name	Date	Scale	③ MOLDED	45P BLACK PVC		G	③	FLY	HELEN	2025, 01. 21		2025, 01. 21	FREE	④ MOLDED	LDPE		G	④						HDMI2.0 AM-AM		⑤ CONNECTOR	HDMI A MALE, GOLD PLATED PIN, BLACK INSULATION, GOLD PLATED SHELL	2	PCS	⑤	⑥ CABLE	[1/0.254BC*1P-D(1/0.254BC)*FAM]45C*1/0.254BC*4C*AL-D(1/0.254BC)*B(1/6*5/0.12AL-MG) BLACK PVC JACKET, OD: 6.0±0.2mm MARKING: High Speed HDMI Cable with Ethernet	L	MM	⑥	ANGLE:					Edition	Sheet	NO.	MATERIAL	DESCRIPTION		QTY.	UNIT					1	1/1
① LABEL	LABEL L*W=80*15 WHIT ELIVI LOGO	1	PCS	①	Quantity	Title/Name, designation, material, dimension etc			Article NO./Reference																																																																					
② DUST CAP	HDMI A MALE DUST CAP	2	PCS	②	Designed by	Checkde by	Approved by - date	File name	Date	Scale																																																																				
③ MOLDED	45P BLACK PVC		G	③	FLY	HELEN	2025, 01. 21		2025, 01. 21	FREE																																																																				
④ MOLDED	LDPE		G	④						HDMI2.0 AM-AM																																																																				
⑤ CONNECTOR	HDMI A MALE, GOLD PLATED PIN, BLACK INSULATION, GOLD PLATED SHELL	2	PCS	⑤																																																																										
⑥ CABLE	[1/0.254BC*1P-D(1/0.254BC)*FAM]45C*1/0.254BC*4C*AL-D(1/0.254BC)*B(1/6*5/0.12AL-MG) BLACK PVC JACKET, OD: 6.0±0.2mm MARKING: High Speed HDMI Cable with Ethernet	L	MM	⑥	ANGLE:					Edition	Sheet																																																																			
NO.	MATERIAL	DESCRIPTION		QTY.	UNIT					1	1/1																																																																			

