



Network Cable Fiber

LinkIT fiber patch OS2 LC/LC 5m

Duplex | SM | LSZH | Blue

Product number: FPD92LULU-050-BLUE

Product Description

This OS2 Duplex fiber optic cable is available in various colors and lengths, featuring LC connectors with UPC polishing on both ends. Designed for singlemode applications with a 9/125 μm core diameter, it supports wavelengths of 1310/1550 nm. The cable offers low insertion loss of ≤ 0.3 dB and an optical return loss of ≥ 55 dB. With a 2mm diameter, the cable is jacketed in LSZH material, providing fire-retardant and halogen-free properties in compliance with IEC safety standards. It withstands temperatures from -40° to $+75^{\circ}\text{C}$, has a bending radius of 20mm, and a tensile load capacity of 150N. Certified to CE and RoHS standards.

Main Specifications

Brand	LinkIT
Color	Blue
Length (m)	5
Category	OS2
Connector type 1	LC
Connector type 2	LC
Polishing contact 1	UPC
Polishing contact 2	UPC
Cable type	Duplex
Number of fibers	2
Wave length (nm)	1310/1550nm
Core Diameter (μm)	9/125 Singlemode

Extended Specifications

Jacket material	LSZH
------------------------	------



Anti-kink sleeve	Moulded
Optical Return Loss (dB)	≥55dB
Insertion Loss (dB)	≤0.3 dB
Operating Temperature	-40° ~ +75°C
Storage Temperature	-40° ~ +75°C
Cable Diameter (mm)	2.0
Fire properties	IEC-60332-3-24, IEC 60332-1-2, IEC 61034, IEC 60754-1
Halogenfree	✓
Oil resistant	✗
Fire retardant version	✓
Bending radius (mm)	20mm
Tensile loads (N)	150N
Certifications	CE, RoHS

Single packaging

Unit	PCE
Quantity	13
Height (cm)	9
Width (cm)	22
Length(cm)	19
Weight (kg)	0,55
Gross Weight (kg)	0,73



Dimensional Sketches

