



## Installation Cable Fiber

### LinkIT fiber OS2 8 Core SC-SC 220m

8x fanout | 9/125 | LSZH | PTPS

Product number: LI-PRSCSCOS2-8C-220

## Product Description

This is a yellow OS2 Singlemode 9/125 fiber cable with eight core fibers. It is preterminated with SC-UPC connectors on both ends (8 connectors on each end). Side A has a pull tube, and side B has a pulling sock. The fanout length is 0.5 meters with a diameter of 0.9 mm. Attenuation is 0.40 dB/km at 1310 nm and 0.30 dB/km at 1550 nm. The maximum tensile load is N1200 (short) and 500 (long), and the maximum bend radius is 20D (dynamic) and 10D (static). It can operate in temperatures from -20°C to +70°C. The cable has a loose tube structure with G652D fibers and a diameter of 6.2 mm. It weighs 67 g per meter and is halogen-free (LSZH), suitable for both indoor and outdoor use.

## Main Specifications

<b>Brand</b>	LinkIT
<b>Color</b>	Yellow
<b>Length (m)</b>	220
<b>Category</b>	OS2 8 fiber
<b>Connector type 1</b>	SC
<b>Connector type 2</b>	SC
<b>Polishing contact 1</b>	UPC
<b>Polishing contact 2</b>	UPC
<b>Number of fibers</b>	8
<b>Core Diameter (um)</b>	9/125

## Extended Specifications

<b>Optical Return Loss (dB)</b>	≥50
<b>Insertion Loss (dB)</b>	≤0.25
<b>Operating Temperature</b>	-20~+70
<b>Storage Temperature</b>	-20~+70
<b>Cable Diameter (mm)</b>	6.2



