



Network Cable Copper

LinkIT ColorFlex S/FTP Cat6a Grey 1m

SlimPatch | AWG 28 | LSZH | OD 5.2mm

Product number: LI-SC6ASFTP-CF-010G

Product Description

This solution is optimal for environments requiring high-density cabling, such as data centers and server rooms. The cable has an outer diameter of 5.2 mm, making it ideal for space-saving installations. Using colorful clips, cables can be easily organized and identified, simplifying maintenance and troubleshooting. To ensure that the cabling meets the highest standards for performance and reliability, the Fluke DSX-8000 Channel Test is utilized. This tool verifies cable installations and contributes to optimal network performance. Additionally, the solution is designed to ensure better airflow and cooling performance, reducing the risk of overheating and improving the overall performance and lifespan of the equipment.

Main Specifications

Brand	LinkIT
Color	Grey
Length (m)	0,5
Category	Cat.6a Slim
Connector type 1	RJ-45 male (8P8C)
Connector type 2	RJ-45 male (8P8C)
Conductor material	Copper
Cable shielding	S/FTP - braided shielding/foiled twisted pairs
Conductor design	Stranded



Extended Specifications

AWG wire size	28
Transmission speed	10Gbps
Frequency (Mhz)	500
Cable structure	4 x 2 AWG 28/7 (Stranded)
Jacket material	LSZH
Anti-kink sleeve	Moulded PVC
Operating Temperature	-20°C ~ 60°C
Cable Diameter (mm)	5.2
Halogenfree	✓
Fire retardant version	✓
Core color 1	Orange
Core color 2	Blue
Core color 3	Green
Core Color 4	Brown
Temperature	Installation: 0°C ~ 50°C
Certifications	CE, REACH, RoHS

Single packaging

Unit	PCE
-------------	-----



Dimensional Sketches

RoHS COMPLIANT		REVISION INFORMATION																																																															
		Rev.	Rev. Date	Modified By	Brief Description																																																												
<p>Overview</p> <ul style="list-style-type: none"> Bandwidth: 500MHz OD: 5.2mm Conductor: 28AWG Approvals: RoHS Connector: 50U" Gold plated RJ45 connector <p>Physical Characteristics</p> <ul style="list-style-type: none"> Cable Type – CAT6A S/FTP Connector Type(s) – RJ45 Wiring Scheme – T568B Temperature Rating <ul style="list-style-type: none"> Installation: 0°C-50°C Operation: -20°C-60°C Voltage Rating – 30V <p>Conductor (Qty. 4 twisted pair)</p> <ul style="list-style-type: none"> Conductor Type – 28AWG(7/0.12±0.008mm), Stranded BC Insulation – FMPE Diameter – 0.80±0.05mm Pair Identification: <ul style="list-style-type: none"> Pair1=Orange, White Pair2=Blue, White Pair3=Green, White Pair4=Brown, White <p>Connector Type (Qty. 2)</p> <ul style="list-style-type: none"> Connector Type – Shielded 8P8C (RJ45) Gender – Male Connector Material – PC Contact Material – Copper Alloy, 50U" Gold Plating Hood Material – PVC MOLDED BOOT. <p>Overall Cable</p> <ul style="list-style-type: none"> Jacket – LSZH Minimum Average Thickness – 0.80mm Outer Diameter – 5.2 ± 0.20mm <p>Electrical Characteristics</p> <ul style="list-style-type: none"> Conductor DC Resistance – 58.3Ω/100m (maximum) Impedance – 100Ω Capacitance – 5900p/100m Propagation Delay – 545ns/100m (maximum) Delay Skew – 45ns/100m (maximum) Pass Fluke DSX 8000 Channel Test 																																																																	
<p>Conductor (Qty. 4 twisted pair)</p> <p>1 — 1 WHITE/ORANGE</p> <p>2 — 2 ORANGE</p> <p>3 — 3 WHITE/GREEN</p> <p>4 — 4 BLUE</p> <p>5 — 5 WHITE/BLUE</p> <p>6 — 6 GREEN</p> <p>7 — 7 WHITE/BROWN</p> <p>8 — 8 BROWN</p> <p>S — S SHIELDED</p>																																																																	
<p>Connector Type (Qty. 2)</p> <p>P1</p> <p>P2 T568B</p>		<p>TOLERANCE:</p> <p>LINEAT: X: ±0.1 ANGULAR: X: ±1°</p> <p>X: ±0.5 X: ±0°30'</p> <p>XX: ±0.05</p> <p>FILLET: R2=RAD.2mm CHAMFER: C0.5=CHAM0.5mm</p> <p>R5=RAD.5mm C1=CHAM1mm</p> <p>XR=MAX RAD.</p>																																																															
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th colspan="6" style="text-align: center;">TOLERANCE GENERALES</th> </tr> <tr> <th>LENGTH(M)</th> <th>0<L<1</th> <th>1≤L<2</th> <th>2≤L<5</th> <th>5≤L<10</th> <th>L≥10</th> </tr> </thead> <tbody> <tr> <td>TOLERANCE</td> <td>+35/-15mm</td> <td>+35/-20mm</td> <td>+35/-30mm</td> <td>±50mm</td> <td>±80mm</td> </tr> </tbody> </table>		TOLERANCE GENERALES						LENGTH(M)	0<L<1	1≤L<2	2≤L<5	5≤L<10	L≥10	TOLERANCE	+35/-15mm	+35/-20mm	+35/-30mm	±50mm	±80mm	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>ITEM NO:</td> <td colspan="3">Fast Tracing CAT.6A S/FTP 28AWG 10G Patch Cable with Colorful Clips</td> <td>DRAWER</td> <td>FW</td> </tr> <tr> <td>TITLE</td> <td colspan="3"></td> <td>DATE</td> <td>20240528</td> </tr> <tr> <td>CUSTOMER</td> <td colspan="3"></td> <td>CHECKED</td> <td>ACE</td> </tr> <tr> <td>MATERIAL</td> <td colspan="3"></td> <td>DATE</td> <td>20240528</td> </tr> <tr> <td>REV.</td> <td>A</td> <td>UNIT</td> <td>MM</td> <td>APPROVED</td> <td></td> </tr> <tr> <td>DRAWING NO:</td> <td colspan="3">8ASFL500712FB 180-40528082</td> <td>DATE</td> <td></td> </tr> <tr> <td>ACAD FILE</td> <td colspan="3">E:A</td> <td colspan="2" style="text-align: center;"> </td> </tr> </table>				ITEM NO:	Fast Tracing CAT.6A S/FTP 28AWG 10G Patch Cable with Colorful Clips			DRAWER	FW	TITLE				DATE	20240528	CUSTOMER				CHECKED	ACE	MATERIAL				DATE	20240528	REV.	A	UNIT	MM	APPROVED		DRAWING NO:	8ASFL500712FB 180-40528082			DATE		ACAD FILE	E:A				
TOLERANCE GENERALES																																																																	
LENGTH(M)	0<L<1	1≤L<2	2≤L<5	5≤L<10	L≥10																																																												
TOLERANCE	+35/-15mm	+35/-20mm	+35/-30mm	±50mm	±80mm																																																												
ITEM NO:	Fast Tracing CAT.6A S/FTP 28AWG 10G Patch Cable with Colorful Clips			DRAWER	FW																																																												
TITLE				DATE	20240528																																																												
CUSTOMER				CHECKED	ACE																																																												
MATERIAL				DATE	20240528																																																												
REV.	A	UNIT	MM	APPROVED																																																													
DRAWING NO:	8ASFL500712FB 180-40528082			DATE																																																													
ACAD FILE	E:A																																																																
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>NO.</th> <th>SPECIFICATION</th> </tr> </thead> <tbody> <tr> <td>4</td> <td>COLORFUL CLIPS</td> </tr> <tr> <td>3</td> <td>RJ45 PLUG: 8P8C 50U" GOLD PLATED TWO-PIECE PLUG; SHIELDED NICKEL PLATING.</td> </tr> <tr> <td>2</td> <td>MOLDED: PVC MOLDED BOOT.</td> </tr> <tr> <td>1</td> <td>CABLE: CAT6A S/FTP [28AWG(7/0.12±0.008BC)+AL/MYLAR]*4+BRAID(18*4/0.12AL-MG) OD=Ø5.2±0.20MM LSZH JACKET.</td> </tr> </tbody> </table>		NO.	SPECIFICATION	4	COLORFUL CLIPS	3	RJ45 PLUG: 8P8C 50U" GOLD PLATED TWO-PIECE PLUG; SHIELDED NICKEL PLATING.	2	MOLDED: PVC MOLDED BOOT.	1	CABLE: CAT6A S/FTP [28AWG(7/0.12±0.008BC)+AL/MYLAR]*4+BRAID(18*4/0.12AL-MG) OD=Ø5.2±0.20MM LSZH JACKET.	<p style="text-align: center;">BOM LIST</p>																																																					
NO.	SPECIFICATION																																																																
4	COLORFUL CLIPS																																																																
3	RJ45 PLUG: 8P8C 50U" GOLD PLATED TWO-PIECE PLUG; SHIELDED NICKEL PLATING.																																																																
2	MOLDED: PVC MOLDED BOOT.																																																																
1	CABLE: CAT6A S/FTP [28AWG(7/0.12±0.008BC)+AL/MYLAR]*4+BRAID(18*4/0.12AL-MG) OD=Ø5.2±0.20MM LSZH JACKET.																																																																

