



Network Cable Copper

LinkIT SlimPatch U/FTP Cat6a Grey 0.5m
LSZH | AWG 28 | Snagless | OD 4.8mm

Product number: LI-SC6AUFTP-0050-G

Product Description

LinkIT Patch Cat.6a cables stand out with their impressive 50-micron gold plating, providing exceptional corrosion protection and optimal signal transmission. Another important feature is support for the PoE++ (Power over Ethernet++) standard, enabling robust power delivery over network cables. This makes the device ideal for power-hungry applications such as cameras, access points, and other devices that require extra power.

The modular plug is equipped with a tangle-free lock that prevents annoying cable tangles and ensures a seamless connection experience. The cable comes with a high-quality clear plug, providing extra strength and protection to the cable ends and ensuring durability and reliability, even in demanding environments.

The cable's performance meets the requirements for Cat.6a (ANSI/TIA-568-C.2 and ISO 11801).

Main Specifications

Brand	LinkIT
Color	Grey
Length (m)	0,5
Category	Cat.6a Slim
Connector type 1	RJ-45 male (8P8C)
Connector type 2	RJ-45 male (8P8C)
Conductor material	Copper
Cable shielding	U/FTP - unshielded/foiled twisted pairs
Conductor design	Stranded



Extended Specifications

AWG wire size	28
Transmission speed	10Gbps
Frequency (Mhz)	500
Cable structure	4 x 2 AWG 28/1 (Solid)
Locking type	Snagless
NVP value	69%
Jacket material	LSZH
Anti-kink sleeve	Assembled
Pin Assignment	1-2;3-6;4-5;7-8
Operating Temperature	-20° ~ 60°C
Cable Diameter (mm)	4.8
Halogenfree	✓
Fire retardant version	✓
Core color 1	White, Orange
Core color 2	White, Green
Core color 3	White, Blue
Core Color 4	White, Brown
Connector contact plating	50u gold plated
Certifications	CE, REACH, RoHS

Single packaging

Unit	PCE
Quantity	1



Dimensional Sketches

RoHS COMPLIANT		REVISION INFORMATION			
Rec.	Rec. Date	Modified By	Brief Description		

Overview

- Bandwidth: 500MHz
- OD: 4.8mm
- Conductor: 28AWG
- Approvals: RoHS
- Connector: 50U" gold plated RJ45 connector

Physical Characteristics

- Cable Type – Cat6A U/FTP
- Connector Type(s) – RJ45
- Wiring Scheme – T568B
- Temperature Rating
 - Installation: 0°C–50°C
 - Operation: -20°C–60°C
- Voltage Rating – 30V

Conductor (Qty. 4 twisted pair)

- Conductor Type – 28AWG(7/0.12±0.008mm), Stranded BC
- Insulation – FMPPE
- Diameter – 0.80±0.05mm
- Pair Identification:
 - Pair1=Orange, White
 - Pair2=Blue, White
 - Pair3=Green, White
 - Pair4=Brown, White

Connector Type (Qty. 2)

- Connector Type – Shielded 8P8C (RJ45)
- Gender – Male
- Connector Material – PC
- Contact Material – Copper Alloy, Gold Plating – 50U"
- Hood Material – Transparent Assemble Boot

Overall Cable

- Jacket – LSZH
- Minimum Average Thickness – 0.55mm
- Outer Diameter – 4.8± 0.20mm

Electrical Characteristics

- Conductor DC Resistance – 80.1Ω/100m (maximum)
- Impedance – 100Ω
- Capacitance – 5600pf/100m
- Propagation Delay – 54ns/100m (maximum)
- Delay Skew – 46ns/100m (maximum)
- Pass DEX 8000 Channel Test
- IEC 60333-1; IEC 60754
- IEEE 802.3af, 802.3at, 802.3bt

	P1	P2	T568B		COLOUR	LENGTH(M)	TOLERANCE
1	Orange	1	WHITE/ORANGE		Gray;	0.5	+20/-15mm
2	Orange	2	ORANGE		White;	1	±20mm
3	Green	3	WHITE/GREEN		Black;	1.5	±20mm
4	Blue	4	BLUE		Green;	2	±30mm
5	White/Blue	5	WHITE/BLUE		Blue	3	±30mm
6	Green	6	GREEN			5	±50mm
7	White/Brown	7	WHITE/BROWN			7	±50mm
8	Brown	8	BROWN			10	±80mm
S	Shielded	S	SHIELDED				

TOLERANCE: ANGULAR X' ±1° X" ±0.25°		CHAMFER: C0.5±CHAM0.5mm C1±CHAM1mm	
LINEAT: X' ±0.1 X" ±0.25	FILET: R2=RAD.2mm R5=RAD.5mm X1=MAX RAD.	ITEM NO:	LinkIT U/FTP Slim CAT.6A 28AWG Patch Cable
COLOR:		DRAWER:	FW
CUSTOMER:		DATE:	20230511
MATERIAL:		CHECKED:	ACE
REV.:	A	DATE:	20230511
DRAWING NO.:	8AUFL480712FB 120-30511113	APPROVED:	
ACAD FILE:	E:\	DATE:	

3	RJ45 PLUG: 8P8C 50U" GOLD PLATED TWO-PIECE PLUG; SHIELDED NICKEL PLATING.
2	MOLDED: TRANSPARENT ASSEMBLE BOOT
1	CABLE: CAT6A U/FTP (28AWG(7/0.12±0.008BC)+AL/MLYAR)*4+DRAIN(7/0.12±0.008TC) OD: 94.8±0.2MM LSZH JACKET.
NO.	SPECIFICATION BOM LIST

