



## Network Cable Copper

### LinkIT SlimPatch U/FTP Cat6a Green 3m

LSZH | AWG 28 | Snagless | OD 4.8mm

Product number: LI-SC6AUFTP-0300-GR

## Product Description

LinkIT Patch Cat.6a cables stand out with their impressive 50-micron gold plating, providing exceptional corrosion protection and optimal signal transmission. Another important feature is support for the PoE++ (Power over Ethernet++) standard, enabling robust power delivery over network cables. This makes the device ideal for power-hungry applications such as cameras, access points, and other devices that require extra power.

The modular plug is equipped with a tangle-free lock that prevents annoying cable tangles and ensures a seamless connection experience. The cable comes with a high-quality clear plug, providing extra strength and protection to the cable ends and ensuring durability and reliability, even in demanding environments.

The cable's performance meets the requirements for Cat.6a (ANSI/TIA-568-C.2 and ISO 11801).

## Main Specifications

<b>Brand</b>	LinkIT
<b>Length (m)</b>	3
<b>Category</b>	Cat.6a Slim
<b>Connector type 1</b>	RJ-45 male (8P8C)
<b>Connector type 2</b>	RJ-45 male (8P8C)
<b>Conductor material</b>	Copper
<b>Cable shielding</b>	U/FTP - unshielded/foiled twisted pairs
<b>Conductor design</b>	Stranded



## Extended Specifications

<b>AWG wire size</b>	28
<b>Transmission speed</b>	10Gbps
<b>Frequency (Mhz)</b>	500
<b>Cable structure</b>	4 x 2 AWG 28/1 (Solid)
<b>Locking type</b>	Snagless
<b>NVP value</b>	69%
<b>Jacket material</b>	LSZH
<b>Anti-kink sleeve</b>	Assembled
<b>Pin Assignment</b>	1-2;3-6;4-5;7-8
<b>Operating Temperature</b>	-20° ~ 60°C
<b>Cable Diameter (mm)</b>	4.8
<b>Halogenfree</b>	✓
<b>Fire retardant version</b>	✓
<b>Core color 1</b>	White, Orange
<b>Core color 2</b>	White, Green
<b>Core color 3</b>	White, Blue
<b>Core Color 4</b>	White, Brown
<b>Connector contact plating</b>	50u gold plated
<b>Certifications</b>	CE, REACH, RoHS

## Single packaging

<b>Unit</b>	PCE
<b>Quantity</b>	1



# Dimensional Sketches

RoHS COMPLIANT		REVISION INFORMATION																													
<p><b>Overview</b></p> <ul style="list-style-type: none"> <li>Bandwidth: 500MHz</li> <li>OD: 4.8mm</li> <li>Conductor: 28AWG</li> <li>Approvals: RoHS</li> <li>Connector: 50U" gold plated RJ45 connector</li> </ul> <p><b>Physical Characteristics</b></p> <ul style="list-style-type: none"> <li>Cable Type – Cat6A U/FTP</li> <li>Connector Type(s) – RJ45</li> <li>Wiring Scheme – T568B</li> <li>Temperature Rating                             <ul style="list-style-type: none"> <li>Installation: 0°C–50°C</li> <li>Operation: -20°C–60°C</li> </ul> </li> <li>Voltage Rating – 30V</li> </ul> <p><b>Conductor (Qty. 4 twisted pair)</b></p> <ul style="list-style-type: none"> <li>Conductor Type – 28AWG(7/0.12±0.008mm), Stranded BC</li> <li>Insulation – FMPPE</li> <li>Diameter – 0.80±0.05mm</li> <li>Pair Identification:                             <ul style="list-style-type: none"> <li>Pair1=Orange, White</li> <li>Pair2=Blue, White</li> <li>Pair3=Green, White</li> <li>Pair4=Brown, White</li> </ul> </li> </ul> <p><b>Connector Type (Qty. 2)</b></p> <ul style="list-style-type: none"> <li>Connector Type – Shielded 8P8C (RJ45)</li> <li>Gender – Male</li> <li>Connector Material – PC</li> <li>Contact Material – Copper Alloy, Gold Plating – 50U"</li> <li>Hood Material – Transparent Assemble Boot</li> </ul> <p><b>Overall Cable</b></p> <ul style="list-style-type: none"> <li>Jacket – LSZH</li> <li>Minimum Average Thickness – 0.55mm</li> <li>Outer Diameter – 4.8± 0.20mm</li> </ul> <p><b>Electrical Characteristics</b></p> <ul style="list-style-type: none"> <li>Conductor DC Resistance – 80.1Ω/100m (maximum)</li> <li>Impedance – 100Ω</li> <li>Capacitance – 5600pf/100m</li> <li>Propagation Delay – 54ns/100m (maximum)</li> <li>Delay Skew – 46ns/100m (maximum)</li> <li>Pass DEX 8000 Channel Test</li> <li>IEC 60333-1; IEC 60754</li> <li>IEEE 802.3af, 802.3at, 802.3bt</li> </ul>		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Rev.</th> <th>Rev. Date</th> <th>Modified By</th> <th colspan="2">Brief Description</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table>				Rev.	Rev. Date	Modified By	Brief Description																						
		Rev.	Rev. Date	Modified By	Brief Description																										
		<p><b>COLOUR</b></p> <p>Gray; White; Black; Green; Blue</p>		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>LENGTH(M)</th> <th>TOLERANCE</th> </tr> </thead> <tbody> <tr> <td>0.5</td> <td>+20/-15mm</td> </tr> <tr> <td>1</td> <td>±20mm</td> </tr> <tr> <td>1.5</td> <td>±20mm</td> </tr> <tr> <td>2</td> <td>±30mm</td> </tr> <tr> <td>3</td> <td>±30mm</td> </tr> <tr> <td>5</td> <td>±50mm</td> </tr> <tr> <td>7</td> <td>±50mm</td> </tr> <tr> <td>10</td> <td>±80mm</td> </tr> </tbody> </table>	LENGTH(M)	TOLERANCE	0.5	+20/-15mm	1	±20mm	1.5	±20mm	2	±30mm	3	±30mm	5	±50mm	7	±50mm	10	±80mm									
		LENGTH(M)	TOLERANCE																												
0.5	+20/-15mm																														
1	±20mm																														
1.5	±20mm																														
2	±30mm																														
3	±30mm																														
5	±50mm																														
7	±50mm																														
10	±80mm																														
<p><b>Overall Cable</b></p> <p>1 — 1 WHITE/ORANGE</p> <p>2 — 2 ORANGE</p> <p>3 — 3 WHITE/GREEN</p> <p>4 — 4 BLUE</p> <p>5 — 5 WHITE/BLUE</p> <p>6 — 6 GREEN</p> <p>7 — 7 WHITE/BROWN</p> <p>8 — 8 BROWN</p> <p>S — SHIELDED</p>		<p><b>TOLERANCE:</b></p> <p>LINEAR: X ±0.1, Y ±0.2, Z ±0.05</p> <p>ANGULAR: X' ±1°, Y' ±0.25°</p> <p>FILET: R2=RAD.2mm, R5=RAD.5mm, X1=MAX RAD.</p> <p>CHAMFER: C0.5=CHAM0.5mm, C1=CHAM1mm</p>																													
<p>3 RJ45 PLUG: 8P8C 50U" GOLD PLATED TWO-PIECE PLUG; SHIELDED NICKEL PLATING.</p> <p>2 MOLDED: TRANSPARENT ASSEMBLE BOOT</p> <p>1 CABLE: CAT6A U/FTP (28AWG(7/0.12±0.008BC)+AL/MLYAR)*4+DRAIN(7/0.12±0.008TC) OD: 94.8±0.2MM LSZH JACKET.</p>		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>ITEM NO:</th> <td>LinkIT U/FTP Slim CAT.6A 28AWG Patch Cable</td> <th>DRAWER</th> <td>FW</td> </tr> <tr> <th>COLOR</th> <td></td> <th>DATE</th> <td>20230511</td> </tr> <tr> <th>CUSTOMER</th> <td></td> <th>CHECKED</th> <td>ACE</td> </tr> <tr> <th>MATERIAL</th> <td></td> <th>DATE</th> <td>20230511</td> </tr> <tr> <th>REV.</th> <td>A</td> <th>APPROVED</th> <td></td> </tr> <tr> <th>DRAWING NO:</th> <td>8AUFL480712FB 120—30511113</td> <th>DATE</th> <td></td> </tr> <tr> <th>ACAD FILE</th> <td>E:\</td> <td></td> <td></td> </tr> </thead> </table>		ITEM NO:	LinkIT U/FTP Slim CAT.6A 28AWG Patch Cable	DRAWER	FW	COLOR		DATE	20230511	CUSTOMER		CHECKED	ACE	MATERIAL		DATE	20230511	REV.	A	APPROVED		DRAWING NO:	8AUFL480712FB 120—30511113	DATE		ACAD FILE	E:\		
ITEM NO:	LinkIT U/FTP Slim CAT.6A 28AWG Patch Cable	DRAWER	FW																												
COLOR		DATE	20230511																												
CUSTOMER		CHECKED	ACE																												
MATERIAL		DATE	20230511																												
REV.	A	APPROVED																													
DRAWING NO:	8AUFL480712FB 120—30511113	DATE																													
ACAD FILE	E:\																														
SPECIFICATION BOM LIST																															

