



Network Cable Copper

LinkIT SlimPatch U/FTP Cat6a White 10m

LSZH | AWG 28 | Snagless | OD 4.8mm

Product number: LI-SC6AUFTP-1000-W

Product Description

LinkIT Patch Cat.6a cables stand out with their impressive 50-micron gold plating, providing exceptional corrosion protection and optimal signal transmission. Another important feature is support for the PoE++ (Power over Ethernet++) standard, enabling robust power delivery over network cables. This makes the device ideal for power-hungry applications such as cameras, access points, and other devices that require extra power.

The modular plug is equipped with a tangle-free lock that prevents annoying cable tangles and ensures a seamless connection experience. The cable comes with a high-quality clear plug, providing extra strength and protection to the cable ends and ensuring durability and reliability, even in demanding environments.

The cable's performance meets the requirements for Cat.6a (ANSI/TIA-568-C.2 and ISO 11801).

Main Specifications

Brand	LinkIT
Length (m)	10
Category	Cat.6a Slim
Connector type 1	RJ-45 male (8P8C)
Connector type 2	RJ-45 male (8P8C)
Conductor material	Copper
Cable shielding	U/FTP - unshielded/foiled twisted pairs
Conductor design	Stranded



Extended Specifications

AWG wire size	28
Transmission speed	10Gbps
Frequency (Mhz)	500
Cable structure	4 x 2 AWG 28/1 (Solid)
Locking type	Snagless
NVP value	69%
Jacket material	LSZH
Anti-kink sleeve	Assembled
Pin Assignment	1-2;3-6;4-5;7-8
Operating Temperature	-20° ~ 60°C
Cable Diameter (mm)	4.8
Halogenfree	✓
Fire retardant version	✓
Core color 1	White, Orange
Core color 2	White, Green
Core color 3	White, Blue
Core Color 4	White, Brown
Connector contact plating	50u gold plated
Certifications	CE, REACH, RoHS

Single packaging

Unit	PCE
Quantity	1



Dimensional Sketches

RoHS COMPLIANT		REVISION INFORMATION																																									
<p>Overview Bandwidth: 500MHz OD: 4.8mm Conductor: 28AWG Approvals: RoHS Connector: 50U" gold plated RJ45 connector</p> <p>Physical Characteristics • Cable Type – Cat6A U/FTP • Connector Type(s) – RJ45 • Wiring Scheme – T568B • Temperature Rating • Installation: 0°C–50°C • Operation: -20°C–60°C • Voltage Rating – 30V</p> <p>Conductor (Qty. 4 twisted pair) • Conductor Type – 28AWG(7/0.12±0.008mm), Stranded BC • Insulation – FMPPE • Diameter – 0.80±0.05mm • Pair Identification: • Pair1=Orange, White • Pair2=Blue, White • Pair3=Green, White • Pair4=Brown, White</p> <p>Connector Type (Qty. 2) • Connector Type – Shielded 8P8C (RJ45) • Gender – Male • Connector Material – PC • Contact Material – Copper Alloy, Gold Plating – 50U" • Hood Material – Transparent Assemble Boot</p> <p>Overall Cable • Jacket – LSZH • Minimum Average Thickness – 0.55mm • Outer Diameter – 4.8± 0.20mm</p> <p>Electrical Characteristics • Conductor DC Resistance – 80.1Ω/100m (maximum) • Impedance – 100Ω • Capacitance – 5600pf/100m • Propagation Delay – 54ns/100m (maximum) • Delay Skew – 46ns/100m (maximum) • Pass DEX 8000 Channel Test IEC 60333-1; IEC 60754 IEEE 802.3af, 802.3at, 802.3bt</p>		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Rev.</th> <th>Rev. Date</th> <th>Modified By</th> <th colspan="2">Brief Description</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table>				Rev.	Rev. Date	Modified By	Brief Description																																		
Rev.	Rev. Date	Modified By	Brief Description																																								
<p>Overall Cable</p> <p>1 — 1 WHITE/ORANGE 2 — 2 ORANGE 3 — 3 WHITE/GREEN 4 — 4 BLUE 5 — 5 WHITE/BLUE 6 — 6 GREEN 7 — 7 WHITE/BROWN 8 — 8 BROWN S — SHIELDED</p>																																											
<p>3 RJ45 PLUG: 8P8C 50U" GOLD PLATED TWO-PIECE PLUG; SHIELDED NICKEL PLATING.</p> <p>2 MOLDED: TRANSPARENT ASSEMBLE BOOT</p> <p>1 CABLE: CAT6A U/FTP (28AWG(7/0.12±0.008BC)+AL/MYLA)*4+DRAIN(7/0.12±0.008TC) OD: 4.8±0.2MM LSZH JACKET.</p>		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">TOLERANCE:</th> <th>COLOUR</th> <th>LENGTH(M)</th> <th>TOLERANCE</th> </tr> </thead> <tbody> <tr> <td>LINEAR: X ±0.1</td> <td>ANGULAR: X' ±1°</td> <td rowspan="7">Gray; White; Black; Green; Blue</td> <td>0.5</td> <td>+20/-15mm</td> </tr> <tr> <td>X ±0.2</td> <td>X' ±0.5°</td> <td>1</td> <td>±20mm</td> </tr> <tr> <td>J0 ±0.05</td> <td>J' ±0.25°</td> <td>1.5</td> <td>±20mm</td> </tr> <tr> <td></td> <td></td> <td>2</td> <td>±30mm</td> </tr> <tr> <td></td> <td></td> <td>3</td> <td>±30mm</td> </tr> <tr> <td></td> <td></td> <td>5</td> <td>±50mm</td> </tr> <tr> <td></td> <td></td> <td>7</td> <td>±50mm</td> </tr> <tr> <td></td> <td></td> <td>10</td> <td>±80mm</td> </tr> </tbody> </table>				TOLERANCE:		COLOUR	LENGTH(M)	TOLERANCE	LINEAR: X ±0.1	ANGULAR: X' ±1°	Gray; White; Black; Green; Blue	0.5	+20/-15mm	X ±0.2	X' ±0.5°	1	±20mm	J0 ±0.05	J' ±0.25°	1.5	±20mm			2	±30mm			3	±30mm			5	±50mm			7	±50mm			10	±80mm
TOLERANCE:		COLOUR	LENGTH(M)	TOLERANCE																																							
LINEAR: X ±0.1	ANGULAR: X' ±1°	Gray; White; Black; Green; Blue	0.5	+20/-15mm																																							
X ±0.2	X' ±0.5°		1	±20mm																																							
J0 ±0.05	J' ±0.25°		1.5	±20mm																																							
			2	±30mm																																							
			3	±30mm																																							
			5	±50mm																																							
			7	±50mm																																							
		10	±80mm																																								
SPECIFICATION BOM LIST		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>ITEM NO:</td> <td>LinkIT U/FTP Slim CAT.6A 28AWG Patch Cable</td> <td>DRAWER:</td> <td>FW</td> </tr> <tr> <td>COLOR:</td> <td></td> <td>DATE:</td> <td>20230511</td> </tr> <tr> <td>CUSTOMER:</td> <td></td> <td>CHECKED:</td> <td>ACE</td> </tr> <tr> <td>MATERIAL:</td> <td></td> <td>DATE:</td> <td>20230511</td> </tr> <tr> <td>REV.</td> <td>A</td> <td>APPROVED:</td> <td></td> </tr> <tr> <td>DRAWING NO:</td> <td>8AUFL480712FB 120—30511113</td> <td>DATE:</td> <td></td> </tr> <tr> <td>ACAD FILE:</td> <td>E:\</td> <td></td> <td></td> </tr> </table>				ITEM NO:	LinkIT U/FTP Slim CAT.6A 28AWG Patch Cable	DRAWER:	FW	COLOR:		DATE:	20230511	CUSTOMER:		CHECKED:	ACE	MATERIAL:		DATE:	20230511	REV.	A	APPROVED:		DRAWING NO:	8AUFL480712FB 120—30511113	DATE:		ACAD FILE:	E:\												
ITEM NO:	LinkIT U/FTP Slim CAT.6A 28AWG Patch Cable	DRAWER:	FW																																								
COLOR:		DATE:	20230511																																								
CUSTOMER:		CHECKED:	ACE																																								
MATERIAL:		DATE:	20230511																																								
REV.	A	APPROVED:																																									
DRAWING NO:	8AUFL480712FB 120—30511113	DATE:																																									
ACAD FILE:	E:\																																										

