



Network Cable Copper

LinkIT ColorFlex U/UTP Cat6a Grey 10m

SlimPatch | AWG 28 | LSZH | OD 5.2mm

Product number: LI-SC6AUUTP-CF-010G

Product Description

This solution is optimal for environments requiring high-density cabling, such as data centers and server rooms. The cable has an outer diameter of 3.6 mm, making it ideal for space-saving installations. Using colorful clips, cables can be easily organized and identified, simplifying maintenance and troubleshooting. To ensure that the cabling meets the highest standards for performance and reliability, the Fluke DSX-8000 Channel Test is utilized. This tool verifies cable installations and contributes to optimal network performance. Additionally, the solution is designed to ensure better airflow and cooling performance, reducing the risk of overheating and improving the overall performance and lifespan of the equipment

Main Specifications

Brand	LinkIT
Color	Grey
Length (m)	7,5
Category	Cat.6a Slim
Connector type 1	RJ-45 male (8P8C)
Connector type 2	RJ-45 male (8P8C)
Conductor material	Copper
Cable shielding	U/UTP - unshielded/unshielded twisted pairs
Conductor design	Stranded



Extended Specifications

AWG wire size	28
Transmission speed	10Gbps
Frequency (Mhz)	500
Cable structure	4 x 2 AWG 28/7 (Stranded)
Jacket material	LSZH
Anti-kink sleeve	Moulded PVC
Operating Temperature	-20°C ~ 60°C
Cable Diameter (mm)	3.6
Halogenfree	✓
Fire retardant version	✓
Core color 1	Orange
Core color 2	Blue
Core color 3	Green
Core Color 4	Brown
Temperature	0°C ~ 50°C
Certifications	CE, REACH, RoHS

Single packaging

Unit	PCE
-------------	-----



Dimensional Sketches

RoHS COMPLIANT		REVISION INFORMATION																															
		Rev.	Rev. Date	Modified By	Brief Description																												
<p>Overview Bandwidth: 500MHz OD: 3.6mm Conductor: 28AWG Approvals: RoHS Connector: 50U" Gold Plated RJ45 Connector</p> <p>Physical Characteristics • Cable Type – CAT6A UTP • Connector Type(s) – RJ45 • Wiring Schema – T568B • Temperature Rating • Installation: 0°C-50°C • Operation: -20°C-80°C • Voltage Rating – 30V</p> <p>Conductor (Qty. 4 twisted pair) • Conductor Type – 28AWG(7/0.12±0.008MM), 8 stranded BC • Insulation – HDPE • Diameter – 0.80±0.05mm • Pair Identification: • Pair1=Orange, Orange-White • Pair2=Blue, Blue-White • Pair3=Green, Green-White • Pair4=Brown, Brown-White</p> <p>Connector Type (Qty. 2) • Connector Type – 8P8C (RJ45) • Gender – Male • Connector Material – PC • Contact Material – Copper Alloy, Gold Plating – 50µm • Hood Material – PVC MOLDED BOOT</p> <p>Overall Cable • Jacket – LSZH • Minimum Average Thickness – 0.80mm • Outer Diameter – 3.6 ± 0.2mm</p> <p>Electrical Characteristics • Conductor DC Resistance – 11.25Ω/100m (maximum) • Impedance – 100Ω • Capacitance – 5600pF/100m • Propagation Delay – 545ns/100m (maximum) • Delay Skew – 45ns/100m (maximum) • Pass Fluke DSX 8000 Channel Test</p>				<p>TOLERANCE:</p> <table border="0"> <tr> <td>LINEAR: X: ±0.1 Y: ±0.5 Z: ±0.35</td> <td>ANGULAR: X: ±1° Y: ±1° Z: ±0.3°</td> </tr> </table> <p>FILL: CHAMP: CH R2=RAD.2mm C0.6=CHAM.5mm R6=RAD.6mm C1=CHAM.1mm XR=MAX 7AD.</p>		LINEAR: X: ±0.1 Y: ±0.5 Z: ±0.35	ANGULAR: X: ±1° Y: ±1° Z: ±0.3°																										
LINEAR: X: ±0.1 Y: ±0.5 Z: ±0.35	ANGULAR: X: ±1° Y: ±1° Z: ±0.3°																																
<p>Colorful Clips</p> <table border="0"> <tr> <td>P1</td> <td>P2 T568B</td> </tr> <tr> <td>1 ——— 1</td> <td>WHITE/ORANGE</td> </tr> <tr> <td>2 ——— 2</td> <td>ORANGE</td> </tr> <tr> <td>3 ——— 3</td> <td>WHITE/GREEN</td> </tr> <tr> <td>4 ——— 4</td> <td>BLUE</td> </tr> <tr> <td>5 ——— 5</td> <td>WHITE/BLUE</td> </tr> <tr> <td>6 ——— 6</td> <td>GREEN</td> </tr> <tr> <td>7 ——— 7</td> <td>WHITE/BROWN</td> </tr> <tr> <td>8 ——— 8</td> <td>BROWN</td> </tr> </table>		P1	P2 T568B	1 ——— 1	WHITE/ORANGE	2 ——— 2	ORANGE	3 ——— 3	WHITE/GREEN	4 ——— 4	BLUE	5 ——— 5	WHITE/BLUE	6 ——— 6	GREEN	7 ——— 7	WHITE/BROWN	8 ——— 8	BROWN	<p>TOLERANCE GENERALES</p> <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>LENGTH(M)</th> <th>0<L<1</th> <th>1≤L<2</th> <th>2≤L<5</th> <th>5≤L<10</th> <th>L≥10</th> </tr> </thead> <tbody> <tr> <td>TOLERANCE</td> <td>+35/-15mm</td> <td>+35/-20mm</td> <td>+35/-30mm</td> <td>±50mm</td> <td>±90mm</td> </tr> </tbody> </table>		LENGTH(M)	0<L<1	1≤L<2	2≤L<5	5≤L<10	L≥10	TOLERANCE	+35/-15mm	+35/-20mm	+35/-30mm	±50mm	±90mm
P1	P2 T568B																																
1 ——— 1	WHITE/ORANGE																																
2 ——— 2	ORANGE																																
3 ——— 3	WHITE/GREEN																																
4 ——— 4	BLUE																																
5 ——— 5	WHITE/BLUE																																
6 ——— 6	GREEN																																
7 ——— 7	WHITE/BROWN																																
8 ——— 8	BROWN																																
LENGTH(M)	0<L<1	1≤L<2	2≤L<5	5≤L<10	L≥10																												
TOLERANCE	+35/-15mm	+35/-20mm	+35/-30mm	±50mm	±90mm																												
<p>4 COLORFUL CLIPS</p> <p>3 RJ45 PLUG: 8P8C 50U" GOLD PLATED TWO-PIECE PLUG.</p> <p>2 MOLDED: PVC MOLDED BOOT.</p> <p>1 CABLE: CAT6A U/UTP 4P/28AWG(7/0.12±0.008BC) OD=Ø3.6±0.2MM LSZH JACKET.</p>		<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>ITEM NO:</td> <td>Fast Tracing CAT.6A U/UTP 28AWG 10G Patch Cable with Colorful Clips</td> <td>DRAWER</td> <td>FW</td> </tr> <tr> <td>TITLE</td> <td></td> <td>DATE</td> <td>20240424</td> </tr> <tr> <td>CUSTOMER</td> <td></td> <td>CHECKED</td> <td>ACE</td> </tr> <tr> <td>MATERIAL</td> <td></td> <td>DATE</td> <td>20240424</td> </tr> <tr> <td>REV.</td> <td>A</td> <td>APPROVED</td> <td></td> </tr> <tr> <td>DRAWING NO:</td> <td>6AU0L380712HB 180--40424171</td> <td>DATE</td> <td></td> </tr> <tr> <td>ACAD FILE</td> <td>E:\</td> <td></td> <td></td> </tr> </table>		ITEM NO:	Fast Tracing CAT.6A U/UTP 28AWG 10G Patch Cable with Colorful Clips	DRAWER	FW	TITLE		DATE	20240424	CUSTOMER		CHECKED	ACE	MATERIAL		DATE	20240424	REV.	A	APPROVED		DRAWING NO:	6AU0L380712HB 180--40424171	DATE		ACAD FILE	E:\				
ITEM NO:	Fast Tracing CAT.6A U/UTP 28AWG 10G Patch Cable with Colorful Clips	DRAWER	FW																														
TITLE		DATE	20240424																														
CUSTOMER		CHECKED	ACE																														
MATERIAL		DATE	20240424																														
REV.	A	APPROVED																															
DRAWING NO:	6AU0L380712HB 180--40424171	DATE																															
ACAD FILE	E:\																																
NO. SPECIFICATION BOM LIST																																	

