



Network Cable Copper

LinkIT ColorFlex U/UTP Cat6a Grey 2m

SlimPatch | AWG 28 | LSZH | OD 5.2mm

Product number: LI-SC6AUUTP-CF-020G

Product Description

This solution is optimal for environments requiring high-density cabling, such as data centers and server rooms. The cable has an outer diameter of 3.6 mm, making it ideal for space-saving installations. Using colorful clips, cables can be easily organized and identified, simplifying maintenance and troubleshooting. To ensure that the cabling meets the highest standards for performance and reliability, the Fluke DSX-8000 Channel Test is utilized. This tool verifies cable installations and contributes to optimal network performance. Additionally, the solution is designed to ensure better airflow and cooling performance, reducing the risk of overheating and improving the overall performance and lifespan of the equipment

Main Specifications

Brand	LinkIT
Color	Grey
Length (m)	2
Category	Cat.6a Slim
Connector type 1	RJ-45 male (8P8C)
Connector type 2	RJ-45 male (8P8C)
Conductor material	Copper
Cable shielding	U/UTP - unshielded/unshielded twisted pairs
Conductor design	Stranded



Extended Specifications

AWG wire size	28
Transmission speed	10Gbps
Frequency (Mhz)	500
Cable structure	4 x 2 AWG 28/7 (Stranded)
Jacket material	LSZH
Anti-kink sleeve	Moulded PVC
Operating Temperature	-20°C ~ 60°C
Cable Diameter (mm)	3.6
Halogenfree	✓
Fire retardant version	✓
Core color 1	Orange
Core color 2	Blue
Core color 3	Green
Core Color 4	Brown
Temperature	0°C ~ 50°C
Certifications	CE, REACH, RoHS

Single packaging

Unit	PCE
-------------	-----



Dimensional Sketches

RoHS COMPLIANT		REVISION INFORMATION																							
Rev.	Rev. Date	Modified By	Brief Description																						
<p>Overview</p> <ul style="list-style-type: none"> Bandwidth: 500MHz OD: 3.6mm Conductor: 28AWG Approvals: RoHS Connector: 50U" Gold Plated RJ45 Connector <p>Physical Characteristics</p> <ul style="list-style-type: none"> Cable Type – CAT6A UTP Connector Type(s) – RJ45 Wiring Schema – T568B Temperature Rating <ul style="list-style-type: none"> Installation: 0°C-50°C Operation: -20°C-80°C Voltage Rating – 30V <p>Conductor (Qty. 4 twisted pair)</p> <ul style="list-style-type: none"> Conductor Type – 28AWG(7/0.12±0.008MM), 8 stranded BC Insulation – HDPE Diameter – 0.80±0.05mm Pair Identification: <ul style="list-style-type: none"> Pair1=Orange, Orange-White Pair2=Blue, Blue-White Pair3=Green, Green-White Pair4=Brown, Brown-White <p>Connector Type (Qty. 2)</p> <ul style="list-style-type: none"> Connector Type – 8P8C (RJ45) Gender – Male Connector Material – PC Contact Material – Copper Alloy, Gold Plating – 50µm Hood Material – PVC MOLDED BOOT <p>Overall Cable</p> <ul style="list-style-type: none"> Jacket – LSZH Minimum Average Thickness – 0.80mm Outer Diameter – 3.6 ± 0.2mm <p>Electrical Characteristics</p> <ul style="list-style-type: none"> Conductor DC Resistance – 11.25Ω/100m (maximum) Impedance – 100Ω Capacitance – 5600pF/100m Propagation Delay – 545ns/100m (maximum) Delay Skew – 45ns/100m (maximum) Pass Fluke DSX 8000 Channel Test 																									
<p>4 COLORFUL CLIPS</p>		<p>TOLERANCE GENERALES</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>LENGTH(M)</th> <th>0<L<1</th> <th>1≤L<2</th> <th>2≤L<5</th> <th>5≤L<10</th> <th>L≥10</th> </tr> </thead> <tbody> <tr> <td>TOLERANCE</td> <td>+35/-15mm</td> <td>+35/-20mm</td> <td>+35/-30mm</td> <td>±50mm</td> <td>±90mm</td> </tr> </tbody> </table>				LENGTH(M)	0<L<1	1≤L<2	2≤L<5	5≤L<10	L≥10	TOLERANCE	+35/-15mm	+35/-20mm	+35/-30mm	±50mm	±90mm								
LENGTH(M)	0<L<1	1≤L<2	2≤L<5	5≤L<10	L≥10																				
TOLERANCE	+35/-15mm	+35/-20mm	+35/-30mm	±50mm	±90mm																				
<p>3 RJ45 PLUG: 8P8C 50U" GOLD PLATED TWO-PIECE PLUG.</p>		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>ITEM NO:</td> <td>Fast Tracing CAT.6A U/UTP 28AWG 10G Patch Cable with Colorful Clips</td> <td>DRAWER</td> <td>FW</td> </tr> <tr> <td>TITLE</td> <td></td> <td>DATE</td> <td>20240424</td> </tr> <tr> <td>CHECKED</td> <td></td> <td>DATE</td> <td>20240424</td> </tr> <tr> <td>CUSTOMER</td> <td></td> <td>APPROVED</td> <td></td> </tr> <tr> <td>MATERIAL</td> <td></td> <td>DATE</td> <td></td> </tr> </table>				ITEM NO:	Fast Tracing CAT.6A U/UTP 28AWG 10G Patch Cable with Colorful Clips	DRAWER	FW	TITLE		DATE	20240424	CHECKED		DATE	20240424	CUSTOMER		APPROVED		MATERIAL		DATE	
ITEM NO:	Fast Tracing CAT.6A U/UTP 28AWG 10G Patch Cable with Colorful Clips	DRAWER	FW																						
TITLE		DATE	20240424																						
CHECKED		DATE	20240424																						
CUSTOMER		APPROVED																							
MATERIAL		DATE																							
<p>2 MOLDED: PVC MOLDED BOOT.</p>		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>REV.</td> <td>A</td> <td>UNIT</td> <td>MM</td> </tr> <tr> <td>DRAWING NO:</td> <td>6AU0L380712HB</td> <td colspan="2"></td> </tr> <tr> <td></td> <td>180--40424171</td> <td colspan="2"></td> </tr> </table>				REV.	A	UNIT	MM	DRAWING NO:	6AU0L380712HB				180--40424171										
REV.	A	UNIT	MM																						
DRAWING NO:	6AU0L380712HB																								
	180--40424171																								
<p>1 CABLE: CAT6A U/UTP 4P/28AWG(7/0.12±0.008BC) OD=Ø3.6±0.2MM LSZH JACKET.</p>																									
NO. SPECIFICATION																									
BOM LIST																									

