



## Network Cable Copper

**LinkIT Flat U/FTP Cat6a Red 0.75m**  
AWG 32 | PVC | 1,85x6mm

Product number: STP-FL6A-00075-RD

### Product Description

High performance flat network cable, space saving. Cable performance exceeds Cat.6a requirements (ANSI / TIA-568-C.2 and ISO 11801) over shorter lengths. Not recommended for use with PoE.

### Main Specifications

|                           |   |
|---------------------------|---|
| <b>Brand</b>              | LinkIT                                  |
| <b>Color</b>              | Red                                     |
| <b>Length (m)</b>         | 0,75                                    |
| <b>Category</b>           | Cat.6a Flat                             |
| <b>Connector type 1</b>   | RJ-45 M (8P8C)                          |
| <b>Connector type 2</b>   | RJ-45 M (8P8C)                          |
| <b>Conductor material</b> | Copper                                  |
| <b>Cable shielding</b>    | U/FTP - unshielded/foiled twisted pairs |
| <b>Cable type</b>         | U/FTP                                   |

### Extended Specifications

|                           |        |
|---------------------------|--------|
| <b>AWG wire size</b>      | 32     |
| <b>Transmission speed</b> | 10Gbps |
| <b>Frequency (Mhz)</b>    | 500    |



|                                  |                             |
|----------------------------------|-----------------------------|
| <b>Cable structure</b>           | 4 x 2 AWG 32/7 Twisted Pair |
| <b>Locking type</b>              | Snagless                    |
| <b>NVP value</b>                 | 69%                         |
| <b>Jacket material</b>           | PVC                         |
| <b>Anti-kink sleeve</b>          | Moulded                     |
| <b>Pin Assignment</b>            | 1-2;3-6;4-5;7-8             |
| <b>Halogenfree</b>               | X                           |
| <b>Oil resistant</b>             | X                           |
| <b>Fire retardant version</b>    | X                           |
| <b>Connector contact plating</b> | 3u gold plated              |
| <b>Certifications</b>            | CE, RoHS                    |

## Single packaging

|                          |      |
|--------------------------|------|
| <b>Unit</b>              | PCE  |
| <b>Quantity</b>          | 1    |
| <b>Height (cm)</b>       | 0,6  |
| <b>Width (cm)</b>        | 7,5  |
| <b>Length(cm)</b>        | 7,5  |
| <b>Weight (kg)</b>       | 0,02 |
| <b>Gross Weight (kg)</b> | 0,02 |

