



## Network Cable Fiber

### LinkIT fiber patch OS2 LC/SC SPX 25.0m

SM | 9/125 | Simplex | LSZH | G657A2 | Yellow

Product number: SULU93L25M

## Product Description

LinkIT fiber patch OS2 cable for smaller losses with small bending diameter (down to 20 mm). For standard fiber cable, bending diameters over 60mm are recommended. The cable has UPC polished connectors for maximum dimming of return light. For 10Gb.

## Main Specifications

|                            |                    |
|----------------------------|--------------------|
| <b>Brand</b>               | LinkIT             |
| <b>Color</b>               | Yellow             |
| <b>Length (m)</b>          | 25                 |
| <b>Category</b>            | OS2                |
| <b>Connector type 1</b>    | LC                 |
| <b>Connector type 2</b>    | SC                 |
| <b>Polishing contact 1</b> | UPC                |
| <b>Polishing contact 2</b> | UPC                |
| <b>Cable type</b>          | Simplex            |
| <b>Number of fibers</b>    | 1                  |
| <b>Core Diameter (um)</b>  | 9/125 - Singlemode |

## Extended Specifications

|                                 |          |
|---------------------------------|----------|
| <b>Transmission speed</b>       | 10Gbps   |
| <b>Jacket material</b>          | LSZH     |
| <b>Anti-kink sleeve</b>         | Moulded  |
| <b>Optical Return Loss (dB)</b> | ≤ 0.3 dB |
| <b>Cable Diameter (mm)</b>      | 2        |
| <b>Halogenfree</b>              | ✓        |



---

|                               |          |
|-------------------------------|----------|
| <b>Fire retardant version</b> | ✓        |
| <b>Certifications</b>         | CE, RoHS |

---

 **Single** packaging

---

|                 |     |
|-----------------|-----|
| <b>Unit</b>     | PCE |
| <b>Quantity</b> | 1   |

---

