



# LinkIT MTP Cassette OS2 AF 2x12xLC low loss AF | 2xMPO connector | 2x12 LC

Product number: LI-MTP2x12LC-OS2AF



### **Product Description**

The LinkIT LI-MTP2x12LC-OS2AF is a high-performance OS2 singlemode fiber cassette designed for high-density data center, telecom, and distribution panel installations. It features two rear 12-fiber MTP Male connectors (USCONEC) and twelve LC Duplex front adapters, supporting 24 individual fiber channels in a compact form factor ( $98.6 \times 146 \times 27$  mm).

Built with durable black plastic housing, the cassette is factory pre-terminated and tested with insertion loss values of <0.35 dB (MTP) and <0.15 dB (LC), ensuring high signal integrity and return loss >55 dB. Both connectors are APC-polished to minimize reflectance. It is optimized for OS2 singlemode applications requiring low loss and high reliability.



# **Main** Specifications


Brand	LinkIT
Measurements (WxHxD)	98.6 × 146 × 27 mm
Polishing contact 1	APC
Polishing contact 2	APC
Material	Plastic
Number of fibers	12
Fibreclass	OS2
Number of outputs	24
Type of inputs	LC Duplex
Polarity Type	A



# **Extended** Specifications

Input	2x MTP Male
Front Connector	12x LC Duplex
Insertion Loss Front	<0.15dB
Connector	
<b>Return Loss Front Connector</b>	>55dB
Rear Connector	2x MTP Male (USCONEC)
Insertion Loss Rear	<0.35dB
Connector	
<b>Return Loss Rear Connector</b>	>55dB
Front Adapter	12x LC Duplex Adaptere
Rear Adapter	MTP Male
Certifications	REACH, RoHS

# **Dimensional** Sketches



T +47 22 90 37 00

M linkit@linkit.eu

W www.linkit.eu